



DECLARATION OF PERFORMANCE

Firestone RubberCover™ EPDM 060

No. DoPRC060v06R-2020-09-09

- 1. Unique identification code of the product-type:**
RubberCover™ EPDM 060
- 2. Identification of the construction product:**
Part number prefix: W56RC6
Lot number: see label
Production date: see print on membrane
- 3. Intended use or uses:**
Non reinforced, black, synthetic roofing membrane made of Ethylene-Propylene-Diene Terpolymer (EPDM) with a nominal thickness of 1.5 mm (MDV); used as a roof waterproofing membrane in fully adhered and ballasted systems as defined by EN 13956.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:**

RubberCover™

| | |
|---|--|
| <i>Manufacturer:</i> Firestone Building Products EMEA Ikaroslaan 75 1930 Zaventem Belgium | <i>Factory:</i> Firestone Building Products Company 1406 US Highway 371 Prescott, AR 71857 USA |
|---|--|
- 5. Contact address of the authorised representative:**
Not applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product:**
System 2+
- 7. Construction product covered by the harmonized standard EN 13956:**
FM Approvals Europe Limited, notified body No. 2809, has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control under system 2+ and issued the EC certificate of conformity of the factory production control 2809-CPR-M0008.

8. Declared performance

| Essential characteristics | | Performance | | Harmonised technical specification |
|--------------------------------|--------------|--------------------|-------------------|------------------------------------|
| | | Value 1.5 mm | Unit | |
| Reaction to fire | EN 13501-1 | E | | EN 13956:2012 |
| External Fire Performance | EN 13501-5 | F ¹⁾ | | |
| Water tightness | EN 1928 | Pass | | |
| Tensile strength | EN 12311-2 | ≥ 7 | N/mm ² | |
| Elongation | EN 12311-2 | ≥ 300 | % | |
| Root resistance | EN 13948 | NPD | | |
| Resistance to static loading | EN 12730 (B) | ≥ 20 | kg | |
| Resistance to impact | EN 12691 (A) | NPD | | |
| | EN 12691 (B) | ≥ 2000 | mm | |
| Tear resistance | EN 12310-2 | ≥ 40 | N | |
| Joint peel resistance | EN 12316-2 | ≥ 50 | N/50mm | |
| Joint shear resistance | EN 12317-2 | ≥ 200 | N/50mm | |
| Durability – UV exposure | EN 1297 | Pass (≥7500h) | | |
| Foldability at low temperature | EN 495-5 | ≤ -45 | °C | |
| Dangerous substances | | None ¹⁾ | | |

- 1) In accordance with EN 13956:2012 the classification of the product in accordance with EN 13501-5 is limited to class F. Classifications of roof build-ups can be obtained separately.
- 2) This product is an article as defined in article 3 of EC regulation No 1907/2006 (REACH). It contains no components which are intended to be released under normal or reasonably foreseeable conditions of use. Based on current knowledge, this product does not contain substances of very high concern as listed in Annex XIV of the REACH regulation or in the "Candidate List of Substances of Very High Concern for Authorisation" published by ECHA in concentrations above 0.1 % (w/w).

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Pascal Meirsschaert
Technical Director
Firestone Building Products EMEA

Brussels, September 2020